

DocuCentre S2520  
A3 Monochrome Desktop Digital  
Multifunction Device



# DocuCentre S2520 A3 Monochrome Desktop Digital Multifunction Device

The perfect solution for small and  
medium-sized businesses



## A3 Monochrome Desktop Digital Multifunction Device Excellent functionality, improved efficiency

A multifunction device equipped with all the essentials to take on any office task. Compact and featuring superb performance, this brand new device is set to dramatically improve efficiency in your office.



# DocuCentre S2520

Combining high productivity with eco-friendly operation.

**Copy Print** B/W: Up to 25ppm (A4)

**Scan** B/W: Up to 28ppm (A4)  
Colour: Up to 28ppm (A4)

**Net Work** Ethernet  
100BASE-TX/10BASE-T

## Speedy operation

### Accelerate office workflows with high-speed output

Take advantage of high-speed printing up to 25 pages/minute simplex and 18 pages/minute duplex. The ideal device for anyone in a rush, the DocuCentre S2520 has a fast First Copy Output Time of 6.5 seconds and boasts a warm-up time of only 19 seconds.

### Improve productivity with fast colour scanning

Enjoy fast scans up to 28 pages/minute, which significantly reduces time spent digitizing large documents resulting in higher productivity.

# Outstanding productivity features

## Convenient ID card copy function

Both sides of a card can be copied onto one side of one single sheet of paper. You can copy up to two cards at the same time.



## Alternating horizontal-vertical stacking

When outputting many copies of the same document — such as materials for meetings — each copy can be stacked in alternating horizontal-vertical orientation to save time when collating.



## Print and copy on heavy paper

Print certificates or greeting cards on 60-216 gsm paper. Printing can be easily customised for nearly any job, eliminating the need to outsource for this purpose.

## Fax more effectively. (Optional)

### Send faxes quickly

Register up to 30 numbers for speed dialling. Legal-size documents can be received on one sheet.

### Redial button

Pressing the redial button displays a list of recent transmissions. Simply select the desired recipient to resend a document.



### Simple broadcast function

Quickly send a document to a group of recipients. This eliminates repetitive tasks when sending the same document to multiple destinations.

## Print multiple pages on one sheet

Different documents can be printed on either side of a piece of paper. Also, by reducing the size of documents, up to eight pages can be printed onto one sheet to help conserve paper and toner.



## Two scanning methods

Choose from two ways to scan, depending on where you are: Pull scan from a PC, or Push scan when at the device. When using Push scan, you can select a resolution between 200 and 600 dpi.



## Eco friendly

### Internationally recognised environmental compliance

The amount of ultrafine particles (UFPs\*) emitted during continuous printing has been reduced by optimising operational settings.

\* Ultrafine particles (UFPs) are tiny particulates less than 100 nanometres in diameter. They are far smaller than the PM2.5 particle class, the regulations for which are becoming stricter from an environmental perspective.

### Eco-friendly and energy saving

DocuCentre S2520 has achieved 1.5 kWh for TEC value\*, conforming to International Energy Star Program standards and reducing power consumption.

\* Value measured by the test defined in International Energy Star Program.

### Adjustable toner output

Toner density is adjustable with six different settings. Printing at lower density saves toner and helps reduce costs.





## Options

On a desk or on the floor.  
Choose the location  
that's best for you.



Base Unit



One Tray Module



One Tray Module  
Two Tray Module

Note: Use Fuji Xerox toner cartridges to ensure optimal performance.

## DocuCentre S2520 Functions & Specifications

### Basic Function / Copy Function

Item	Description
	DocuCentre S2520
Type	Desktop
Memory capacity	512 MB (Max : 512 MB)
Scan Resolution	600 x 600 dpi
Print Resolution	600 x 600 dpi
Warm-up Time	19 seconds or less (20 degrees Celsius room temperature)
Original Size	Maximum of 297 x 432 mm (A3,11 x 17") for both Sheet and Book
Paper Size	Max 297 x 432 mm, A3, 11 x 17", Bypass Tray : 297 x 432 mm, A3, 11 x 17"
	Min A5, Bypass Tray : 127 x 98 mm
	Image loss width Lead Edge : 5.5 mm, Trail Edge : 6.0 mm, Right & Left Edges : 5.5 mm
Paper Weight <sup>1</sup>	Tray 1 60 to 90 gsm
	Tray 2, 3, 4 (Option) 60 to 216 gsm
	Bypass Tray 60 to 216 gsm
First Copy Output Time	6.5 seconds or less (A4 LEF)
Continuous Copy Speed <sup>2</sup>	A4 LEF/B5 LEF 25 ppm, In Duplex : 18 ppm
	A4 16 ppm, In Duplex : 10 ppm
	B4 15 ppm, In Duplex : 9 ppm
	A3 13 ppm, In Duplex : 8 ppm
Paper Tray Capacity <sup>3</sup>	Standard Tray1 : 250 sheets, Bypass Tray : 100 sheets
	Optional One Tray Module (Tray2) : 500 sheets Two Tray Module (Tray3 + Tray4) : 1000 sheets
	Max 1850 sheets (Tray1 + Tray2 + Tray3 + Tray4 + Bypass Tray)
Output Tray Capacity <sup>3</sup>	250 sheets (A4 LEF)
Power Source	AC220-240 V +/- 10 %, 6 A, 50 / 60 Hz common
Maximum Power Consumption	AC 220V: 1.3kW or less AC 240V: 1.4kW or less Low Power mode: 14W or less Sleep mode: 2W or less
Dimensions	W 595 x D 584 x H 569 mm
Weight <sup>4</sup>	33 kg

\*1: It is recommended to use Fuji Xerox recommended paper. Correct print output may not be possible depending on the requirement. \*2: The speed may be reduced due to the image quality adjustment. The performance may be reduced depending on the paper type. \*3: When Using 80 gsm paper. \*4: Excluding Toner Cartridge.

### Fax Function (Optional)

Item	Description
Original Size	Max : A3
Recording Paper Size	Max : A3, Min : A4
Transmission Time*	2 seconds and more but fewer than 3 seconds
Transmission Mode	Super G3 / G3 ECM / G3 (ITU-T)
Applicable Lines	PSTN / PBX, 1 port

\*: When A4 size document with approximately 700 characters is transmitted in standard image-quality (8x3.85 lines/mm) and in high-speed mode (28.8kbps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contents of the document, the type of device receiving the fax, and line condition.

#### Notes

- 1) If the storage media (such as hard disk drives) of the base unit fail, loss of received data, accumulated data, registered setting data, etc. may occur. In no event shall Fuji Xerox be liable for any damages whatsoever arising from loss of data.
- 2) Functional spare parts will be available for at least 7 years after the product is no longer manufactured.
- 3) The product specifications, appearance and other details in this catalog are subject to change without notice for improvements.

Other company names or product names are registered trademarks or trademarks of each company.

**Reproduction Prohibitions** Please note that reproduction of the following is prohibited by law : Domestic and foreign currencies, government-issued securities, and national bonds and local bond certificates. Unused postage stamps, post cards, etc. Certificate stamps stipulated by law. Reproducing works forming the subject matter of copyright (literary works, musical works, paintings, engravings, maps, cinematographic works, drawings, photographic works, etc.) is not permitted unless the reproduction is for the purpose of personal use, family use or other similar uses within a limited circle.

### Print Function

Item	Description
Type	Built-in type
Continuous Print Speed <sup>1</sup>	Same as the Basic Specifications / Copy Function
Print Resolution	600 x 600 dpi
Page Description Language	FX HBPL (Host Based Print Language)
Operation System <sup>2</sup>	Windows® XP (32bit), Windows Server® 2003 (32bit), Windows Vista® (32bit) Windows Server® 2008 (32bit), Windows® 7 (32bit), Windows® 8 (32bit) Windows® 8.1 (32bit), Windows® XP Professional (64bit) Windows Server® 2003 (64bit), Windows Vista® (64bit) Windows Server® 2008 (64bit), Windows® 7 (64bit), Windows Server® 2008 R2 (64bit) Windows® 8 (64bit), Windows Server® 2012 (64bit), Windows® 8.1 (64bit) Windows Server® 2012 R2 (64bit)
Interface	USB2.0, Ethernet 100BASE-TX / 10BASE-T

\*1: The speed may be reduced due to image quality adjustment. Print speed may also drop depending on the documents.  
\*2: Please refer to the Fuji Xerox web site for the latest supported operating systems.

### Scan Function

Item	Description
	DocuCentre S2520
Type	Colour Scanner
Scan Resolution	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 200 dpi
Scan Speed <sup>1</sup>	B / W : 28 ppm, Colour : 28 ppm (Fuji Xerox Standard Paper (A4 LEF), 200dpi)
Interface	USB2.0, Ethernet 100BASE-TX / 10BASE-T

\*: The scanning speed varies depending to documents. Fuji Xerox Standard Document (A4), 200 dpi, using TWAIN driver (USB).

### Duplex Automatic Document Feeder

Item	Description
	DocuCentre S2520
Original Size	Max : A3, 11 x 17", Min : A5
Paper Weight	38 to 128 gsm (2 Sided : 50 to 128 gsm)
Capacity <sup>1</sup>	110 sheets
Feeding Speed (A4 LEF Simplex)	25 ppm (A4 LEF, 1 Sided) 18 ppm (A4 LEF, 2 Sided)

\*: When Using 80 gsm paper.

### Accessories

Item	Product Code	Capacity
Fax Kit	EL201137	-
One Tray Module	EL201138	500 sheets
Two Tray Module (requires One Tray Module)	EC102050	2 x 500 sheets
Cabinet (requires One Tray Module)	EL200737	-
Tray Lock	EL201058	-

### Consumables

Item	Product Code	Yield
Toner Cartridge <sup>1</sup>	CT202384	9,000 pages
Drum Cartridge	CT351075	68,000 pages

<sup>1</sup>Average standard A4 pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and media used.



#### For Your Safety

Before using the product, read the Instruction Manual carefully for proper use. Use the product with the power source and voltage specified. Be sure to establish ground connection. Otherwise, electronic shock may result in the case of a failure or short circuit.

For more information or detailed product specification,  
please call or visit us at

## Fuji Xerox Asia Pacific Pte Ltd

14a Rodborough Road Frenchs Forest NSW 2086  
Australia 1300 793 769

New Zealand 0800 993 769

[www.fujixeroxprinters.com.au](http://www.fujixeroxprinters.com.au)

[www.fujixeroxprinters.co.nz](http://www.fujixeroxprinters.co.nz)

